









POWER LINE
Release and lubrication – the complete package

EXPERT LINE
The specialist in action

	HeBoCoat® PL-W 130	HeBoCoat® PL-W 200	HeBoCoat® PL-W 250	HeBoCoat® PL-W 300	HeBoCoat® PL-W 310	HeBoCoat® PL-WF 125	HeBoCoat® EL-W 250	HeBoCoat® EL-W 300
Base	water	water	water	water	water	water	water	water
Binder	Boron compounds	Polymer	Aluminium oxide	Polymer	none	Boron compounds / Phosphate	Aluminium oxide	none
Binder stability	> 300 °C	< 300 °C	> 300 °C	< 300 °C	n.a.	> 300 °C	< 300 °C	n.a.
Solid content	16 %	23 %	37 %	32 %	30 % +/-1	17 %	37 %	30 %
Boron nitride	13 %	20 %	25 % *	30 %	30 % +/-1	13 %	25 %	29 %
Colour	White	White to amber	Grey	White	White	White	White	White
Surface adhesion	+	+	+	+	o	++	+	+
Release action	++	++	++	++	++	+	++	++
Lubrication effect	++	++	o	o	+	+	+	o
Application								

++ very good / + good / o moderate

* The product contains boron nitride as well as other ceramic components.

The data quoted in this leaflet are typical for the material. They are intended as a guide only and should not be used in preparing detailed specifications. Actual product data may deviate from the figures given. We reserve the right to alter product data within the scope of technical progress and new developments. Since processing involves factors that are beyond our control, recommendations made in this leaflet should be checked by preliminary trials, especially for third party applications. These recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties' rights and, if necessary, from clarifying the situation.

Henze BNP AG . Phone: +49 8374.589 97-0 . Fax: +49 8374.589 97-99 . info@henze-bnp.de . www.henze-bnp.de